

2/19/18
DIALOG(R)File 347:JAPIO
(c) 2003 JPO & JAPIO. All rts. reserv.

06276506 **Image available**
BEARING SEAL DEVICE FOR WATER PUMP, BEARING FOR WATER PUMP AND WATER PUMP
FOR WATER-COOLED ENGINE FOR AUTOMOBILE

PUB. NO.: 11-218095 [JP 11218095 A]
PUBLISHED: August 10, 1999 (19990810)
INVENTOR(s): MIYAKE NOBUHIKO
 IWAKIRI SHIGERU
APPLICANT(s): NIPPON SEIKO KK
APPL. NO.: 10-315465 [JP 98315465]
FILED: October 19, 1998 (19981019)
INTL CLASS: F04D-029/12; F16C-033/78; F16C-033/80; F16J-015/32

ABSTRACT

PROBLEM TO BE SOLVED: To provide a **bearing seal** device for a water pump, a **bearing** for a water pump, and a water pump for a water-cooled engine for an automobile to approximately reliably prevent permeation of cooling water and steam about to permeate the internal part of a **bearing** and prevent outflow of grease in a **bearing**.

SOLUTION: A **seal** ring on the impeller side comprises a **seal** ring 151 on the outer ring consisting of a reinforcing ring, a first auxiliary lip 1512, a main lip 1513, both formed of an elastic body, such as rubber or synthetic resin, and a second auxiliary lip 1514 positioned further on the outside diameter side than the main lip 1513; and a **seal** ring 152 on the haft side consisting of a first cylinder part 1521 securely fitted in a **shaft** body, an intermediate part 1522 extending to the outside diameter side therefrom, and a second cylinder part 1523 axially extending in succession thereto, and rotated with a **shaft** body. In this case, the main lip 1513 makes slide contact with the outer peripheral surface of the first cylinder part 1521 of the **seal** ring 152 on the **shaft** side, the first auxiliary lip 1512 makes slide contact with the outer peripheral surface of a rotary member located further inside in an axial direction than the main lip 1513. The second auxiliary lip 1514 makes slide contact with the **seal** ring 152 on the **shaft** side in a position on the further outside diameter side than the main lip 1513, and the part, extending to the outer diameter side, of the **seal** ring 152 on the **shaft** side constitutes a labyrinth **seal** between the **seal** ring 151 on the outer side and the outer ring 101.

COPYRIGHT: (C)1999,JPO

C:\Program Files\Dialog\DialogLink\Graphics\16.bmp

